




LX900 & LX400

Full Color Digital Inkjet Label/Barcode Printers



Introducing the affordable LX900 and the low-cost LX400 digital desktop inkjet label/barcode printers from Fernqvist that print full color labels on demand.

The printers are durable, suitable for both industrial and retail environments. They can handle all of your packaging and identification duties. Print quantities from one label to thousands per day on rolls. Powered by Lexmark reliable time tested technology, we're sure the LX900 or LX400 will be your choice for your day-to-day full color label production.



The LX900 and LX400 will enhance your operation. Produce quick, clean color labels when and where they are needed. Save money by reducing your label inventory and time in managing projects. The state of the art LX900 is equipped with three built in printer resolutions so you can select the combination of print quality and speed that best fits your application. The LX400 is priced right for high quality yet economical digital printing.



Print from the LX900 and LX400 printers on to a variety of label material from Fernqvist. Paper and synthetic labels are available in hundreds of sizes. Semigloss, high gloss paper and poly film is a popular choice for the smudge resistant and water safe features they offer.

The complete LX printing systems include ink cartridges (individual cyan, magenta, yellow, and black cartridges for LX900 and one CMY cartridge for LX400), and NiceLabel SE Primera Edition by NiceWare Software (upgrades available to NiceLabel Express or Pro.) Supplies can be changed in seconds and have a long shelf life for storage.



The LX900 and LX400 can be used either in the office or the most challenging shop/warehouse environments. Label material is stored within the case ensuring it stays clean.

Call today, 800-426-8215 or 800-771-9316 (New York) to find out how you can benefit from the revolutionary LX900 or LX400 full color digital inkjet label/barcode printer.



Label solutions for every industry :: food :: manufacturing :: medical :: nursery :: retail :: shipping ::

Technical Specifications	LX900	LX400
Print Method:	Inkjet	Inkjet
Print Resolution:	up to 4800dpi,	2400x1200dpi
Ink Cartridge:	Color (individual C, M, Y, K cartridges)	Color (CMY)
Colors:	16.7 Million	16.7 Million
Color Matching:	Z-Color™ Color Matching Software	Z-Color™ Color Matching Software
Print Width:	8.25" (210mm)	.75"-4" (19mm-101.6mm)
Print Length:	NA	.75" - 24" (19mm-609mm)
Media Width:	8.375" (213mm)	1.0" - 4.25" (25.4mm-108mm)
Media Types:	Roll-fed pressure sensitive labels, roll-fed tags	Roll-fed pressure sensitive labels, roll-fed tags, fan fold labels and tags
Media Sensing:	Moveable see-through sensor for diecut labels; Reflective for labels and tags with black stripe; Continuous label stock; Preprinted label stock	Moveable see-through sensor for diecut labels; Reflective for labels and tags with black stripe; Continuous label stock; Preprinted label stock
Supply Roll:	6" (152mm) maximum diameter on 3" (76mm) core	5" (127mm) maximum diameter on 2" (50.8mm) core
Ink Level Warning:	Calculates actual number of prints remaining based upon ink usage of graphics being printed (Patent Pending)	Calculates actual number of prints remaining based upon ink usage of graphics being printed (Patent Pending)
Indicator Lights:	Power, Pause, Ink	Power, Ink
Controls:	Pause, Feed, Unload	Pause, Load/Feed, Unload
Operating Systems:	Windows XP/Vista® or Windows 7 Mac OS X v10.5 or higher	Windows XP/2000 Mac OS X v10.2 or higher
Recommended Minimum System:	For PC: Pentium IV computer or better, 512MB RAM, 5GB free hard drive space, USB 2.0 (recommended) For Mac: 700 Mhz G4 or higher with 512MB RAM, 5GB free hard drive space, USB 2.0 (recommended)	For PC: Pentium IV computer or better, 512MB RAM, 5GB free hard drive space, USB 2.0 (recommended) For Mac: 700 Mhz G4 or higher with 512MB RAM, 5GB free hard drive space, USB 2.0 (recommended)
Label Design Software:	NiceLabel SE Primera Edition included. Can also be used with most other popular label design software programs.	NiceLabel SE Primera Edition included. Can also be used with most other popular label design software programs.
Electrical Rating:	12VDC, 5.0A	12VDC, 5.0A
Power Requirements:	100-240VAC, 50/60 Hz, 60 watts	100-240VAC, 50/60 Hz, 60 watts
Certifications:	UL, UL-C, CE, FCC Class B	UL, UL-C, CE, FCC Class A
Weight:	36.5 lbs (16.6 kg)	7 lbs (3.2 kg)
Dimensions:	Width 17.25", Depth 17.25", Height 9.1" (438mmW x 438mmD x 231mmH)	Width 10.4", Depth 15.3", Height 7.1" (closed), 17.4" (open) (264mmW x 389mmD x 180mmH closed, 442mmH open)
Options:		Media Cutter #74263

The Fernqvist Mission: Creating Customers for the Long Term!

1245 Spacepark Way, Ste C, Mountain View, CA 94043 toll free: 800-426-8215 local: 650-428-0330 fax: 650-428-1615
845 Marconi Avenue, Ste B, Ronkonkoma, NY 11779 toll free: 800-771-9316 local: 631-738-8050 fax: 631-738-0052
email: sales@fernqvist.com website: www.fernqvist.com

